


DCDB

Equipment	Power Supply Circuit	
Dimension	Customized As Per OEM	
Mounting Arrangement	Floor Type/Wall mount/Pole mount	
Colour	RAL 7035 / Customized	
Ingress Protection	IP 55	
Door Lock	3pt /4pt Lock & Provision Of Pad Lock	
Cable Entry	Provision Of Sufficient Cable Entry Through Roxtec / Wallmax And Cable Glands	
Lightning	DC CFL / LED Operated On 48V DC	
Door Sealing	Provision Of Door Sealed With Proper EPDM Gasket / PU Gasket	
DCDB	DCDB Arrangement Mounted On 19" Rail With Terminal Block And Earthing Busbar	
Earthing	Earthing Bolts Are Provided For Earthing	
Earthing (Equipment)	Provision Of Equipment Earthing Thru Suitable Busbar	
Lifting Arrangement	Provision of Lifting Bracket to lift the Under Ground Vault	
Grouting Arrangement on Bracket	Anchor Fastener	
Manual / Labels / Stickers	Proper Labels & Sticker Are Provided	
Packing	Corrugated Box	



Available Range Of DCDB

Height (mm)	Width (mm)	Depth(mm)
200	250	150
250	300	150
300	300	200
400	350	200
450	450	250
550	450	300

