



SVARN
Inspired by possibilities

THREE ALUMINUM PVC INSULATED CABLE

PRODUCT DETAILS

3 Core, Aluminum Conductor, PVC Insulated, Un-armoured / GS Round wire Armoured / GS Flat Strip Armoured, PVC Outer Sheath Cable conforming to IS 1554 Part-1 with up to date amendment.

- Voltage Rating : 1100 Volts
- Temperature Rating : -5°C to +70°C/85°C
- UV Resistance
- RoHS Compliant



TECHNICAL SPECIFICATIONS

Material		Ref. Spec
Conductor	Aluminum Conductor	IS 8130
Insulation	Extruded PVC Type -A, Extruded HR PVC Type - C	IS 5831
Insulation Colour	Red, Yellow & Blue	IS 1554 Part-1
Inner Sheath	Extruded PVC Type ST-1, Extruded HR PVC Type ST-2	IS 5831
Armouring (as applicable)	GS Round Wire GS Flat Strip	IS 3975
Outer Sheath	Extruded PVC Type ST-1, Extruded HR PVC Type ST-2	IS 5831
Colour	Black or optional	
Special Properties (on request)	Flame Retardant Flame Retardant Low Smoke Flame Retardant Low Smoke Zero Halogen	

Cross Sectional Area (sqmm)	Insulation Thickness (Nominal)	Inner Sheath Thickness (Minimum)	Unarmoured Cables (YY)		Flat Strip Armoured Cable (YFY)			Round Wire Armoured Cable (YVY)			Current Rating		DC Resistance At 20°C (Max)	AC Resistance
			Outer Sheath Thickness (Nominal)	Overall Diameter (Approx)	Armour Dimension (Flat Strip)	Outer Sheath Thickness (Minimum)	Overall Diameter (Approx)	Armour Dimension (Round Wire)	Outer Sheath Thickness (Minimum)	Overall Diameter (Approx)	Ground	Air		
4	1.0	0.3	1.8	16	-	-	-	1.4	1.24	18	28	23	7.41	8.89
6	1.0	0.3	1.8	18	-	-	-	1.4	1.24	19	35	30	4.61	5.53
10	1.0	0.3	1.8	19	-	-	-	1.4	1.40	21	46	40	3.08	3.70
16	1.0	0.3	1.8	19	4 x 0.80	1.40	20	1.6	1.40	21	60	51	1.91	2.29
25	1.2	0.3	2.0	22	4 x 0.80	1.40	23	1.6	1.40	23	76	70	1.20	1.44
35	1.2	0.3	2.0	24	4 x 0.80	1.40	24	1.6	1.40	26	92	86	0.868	1.04
50	1.4	0.3	2.0	27	4 x 0.80	1.56	27	1.6	1.56	29	110	105	0.641	0.769
70	1.4	0.4	2.2	30	4 x 0.80	1.56	31	2.0	1.56	33	135	130	0.443	0.532
95	1.6	0.4	2.2	34	4 x 0.80	1.56	35	2.0	1.56	37	165	155	0.320	0.384
120	1.6	0.4	2.2	37	4 x 0.80	1.72	37	2.0	1.72	39	185	180	0.253	0.304
150	1.8	0.5	2.4	40	4 x 0.80	1.88	41	2.0	1.88	43	210	205	0.206	0.247
185	2.0	0.5	2.6	44	4 x 0.80	1.88	46	2.5	2.04	49	235	240	0.164	0.197
240	2.2	0.6	2.8	50	4 x 0.80	2.20	51	2.5	2.20	54	275	280	0.125	0.150
300	2.4	0.6	3.0	55	4 x 0.80	2.36	56	2.5	2.36	59	305	315	0.100	0.120
400	2.6	0.7	3.4	62	4 x 0.80	2.52	63	3.15	2.68	68	335	375	0.0778	0.0934
500	3.0	0.7	3.6	69	4 x 0.80	2.84	70	3.15	2.84	75	370	425	0.0605	0.0726
630	3.4	0.7	4.0	77	4 x 0.80	3.00	78	4.0	3.00	84	405	480	0.0469	0.0563

This document is the property of SVARN No one is to retain, pass on amend or otherwise use this document, unless specially authorized/permitted by Chief Executive Officer of SVARN



SVARN GROUP

1800-121-222-999 | info@svarn.com | www.svarn.com

TELECOM | AUTOMOTIVE | DEFENCE | RAILWAYS | POWER | PROJECTS