

UNDER GROUND TELECOM VAULT

Equipment Available In Size Equipment Mounting	SMPS / PIU / Battery / Combo Power Unit 20U / 24U / 32U / 40U
19" Mounting Dimension	Customized As Per OEM
Mounting Arrangement	Floor Type
Colour	RAL 7035 / Customized
Ingress Protection	lp67
Cooling Solution	Fan Filter Arrangement
Fan	48V DC Axial Fans
Fan Tray	Fan Tray With Smart Controller
Smart Controller	Controls Fan Management System & Provide PFC Alarms For 1. High Temperature 2. Smoke Sensor 3. Fan Failure 4. Door Open
Temperature	Fan Filter Arrangement Are Generally Designed To Maintain 5°C Temp
Door Lock	Single Point Lock / Latch Lock / Cam Lock & Provision Of Pad Lock
Cable Entry	Provision Of Sufficient Cable Entry Through Roxtec / Wallmax & Cable Glands
Lightning	DC CFL / LED Operated On 48V DC
Filter	G3 / G4 Filter With Aluminium Frame For Dust Protection
Door Sealing	Provision Of Door Sealed With Proper EPDM Gasket / PU Gasket
DCDB	DCDB Arrangement Mounted On Side Wall With Terminal Block And Earthing Busbar
Earthing (Vault)	Earthing Bolts Are Provided For Earthing
Earthing (Equipment)	Provision Of Equipment Earthing Through Suitable Busbar
Lifting Arrangement	Provision Of Lifting Bracket To Lift The Under Ground Vault
Grouting Arrangement On Bracket	Anchor Fastener
Manual / Labels / Stickers	Proper Labels & Sticker Are Provided
Packing	Wooden Pallet & Wooden Box





