





General

Our Ruggedised 19" Outdoor EMI-EMC
Enclosure has been designed using the
latest software, with both structural and
thermal design verification carried out using
design simulation software. The Enclosures
are manufactured in a state-of-the-art
facility and powder-coated on a
conveyorised and automated paint line after
being subjected to seven tank
pre-treatment. They provide excellent field
performance and reliability, as per MIL
Standards. They are equipped with shelves,
whose size can be varied as per specific
customer requirements.

Specifications

Dimensions.

Height: 1216 (±5) mm, Width: 600 (±2) mm,

Depth: 900 (0, -5) mm.

Weight: Bare Rugged Enclosure including all sub


parts: < 100 kg.

Finish

- Chromate conversion coating as per
 MIL DTL 5541 Type 2 Class 3 before painting.
- External finish with polyurethane paint.
- Camouflage pattern/colours of choice.

Material

- Rugged Enclosure Frame Assembly made of Aluminium HE 30 Grade/AL. Alloy 5052.
- All fasteners made of stainless steel grade A2-70.





EMI-EMC Features.

- Conforms to JSS 55555 standards.
- Doors and Side Panels are designed to provide required EMI/EMC protection to meet MIL-STD-461 E/F.
- Features Honeycomb Mesh, Air inlet and Outlet, and Openable Filters.
- Configured to provide 60dB isolation.

Thermal Management.


- Equipped with fan tray control unit to meet thermal requirements.
- Heat dissipation capability: 700 W, which can be customised as per requirement.


Lifting and Mounting.

- \bullet Lifting with 4 x M10 as per DIN 580, capable of lifting Enclosures of up to 300 kg.
- Metal base, frame mounted Rugged Enclosure with wire rope isolators/shock mount, featuring vertical wire rope isolators/shock mount support arrangement.

Other Features.

- IP 55 complied Enclosure.
- Legible laser engravings as per requirement.
- Provision for mounting LEDs as per requirement.
- Doors equipped with spring-loaded, stainless steel rotary draw latches with a locking mechanism on both doors, suitable for rugged applications.
- Design can be customised to meet every customer's requirement.







CORPORATE OFFICE: Plot No. 1, Site No. 1, 14/3, Mathura Road, Faridabad-121003 (Haryana), India | P: 0129-4294200
74th Milestone, Delhi-Mathura Road, before Hodal Toll Plaza, Distt. Palwal-121005 (Haryana), India
Plot No. 68, 69, 71, 72 & 73, Sector-5, IIE, Sidcul, Haridwar-249403 (Uttarakhand), India

+1800-121-222-999 km helpline@svarn.com # www.svarn.com